

## 5-15mins



- ① 高温性能好，40°C以下无需空调冷却，节省能源
- ② PACK模块化标准设计，可以自由组合,易运维
- ③ 循环长寿命，3000次@0.5C/0.5C，80%DOD，25°C
- ④ 触摸LCD直观显示各类参数、记录、状态、告警等内容
- ⑤ 支持多组并机，柜级消防
- ⑥ 支持二线线设计，满足UPS机型要求
- ⑦ 三级BMS管理，从电芯到系统，层层保障系统安全可靠运行
- ⑧ 能量密度高，比铅酸蓄电池节省70%占地面积

### 产品参数

产品型号	CF24050U	CF48050U	CF486100U	CF512100U
电芯材料			磷酸铁锂	
标称电压	240Vdc	480Vdc	486.4Vdc	512Vdc
额定充电电压	262.5Vdc	525Vdc	532Vdc	560Vdc
标称容量	50Ah/12kWh	50Ah/24kWh	100Ah/48.64kWh	100Ah/51.2kWh
自放电率			≤3% (0~30°C/3个月)	≤3% (0~30°C/3个月)
标准放电电流	50A连续放电(1C)	50A连续放电(1C)	100A连续放电(1C)	100A连续放电(1C)
最大放电电流	300A连续放电(6C)	300A连续放电(6C)	600A连续放电(6C)	600A连续放电(6C)
标准充电电流	25A(0.5C)	25A(0.5C)	50A(0.5C)	50A(0.5C)
最大充电电流	50A(1C)	50A(1C)	100A(1C)	100A(1C)
循环寿命			3000次 @80%DOD, 0.5C/0.5C	
通信接口			CAN; RS485; 干接点	
保护功能			过温, 过流, 短路, 过充, 过放等	
尺寸 (W*D*H)	600*800*1400mm	600*800*2000mm	600*800*2200mm	600*800*2200mm
认证			UN	
环境				
存储温度			0~40°C	
运行温度			15~45°C(推荐20~25°C运行)	
相对湿度			5~95%	
海拔			≤2000m	
电芯规格参数				
标称容量	50Ah	50Ah	50Ah	50Ah
标称电压	3.2Vdc	3.2Vdc	3.2Vdc	3.2Vdc
工作电压范围	2.5~3.6Vdc	2.5~3.6Vdc	2.5~3.6Vdc	2.5~3.6Vdc
电池模块规格参数				
配置	1P15S	1P15S	2P20S/2P18S	2P20S
标称电压	48Vdc	48Vdc	64/57.6Vdc	64Vdc
工作电压范围	42~52.5Vdc	42~52.5Vdc	56~70Vdc/50.4~63Vdc	56~70Vdc
电池簇规格参数				
配置	1P75S	1P150S	2P152S	2P160S
标称容量	50Ah	50Ah	100Ah	100Ah
标称电压	240Vdc	480Vdc	486.4Vdc	512Vdc
工作电压范围	210~262.5Vdc	420~525Vdc	425.6~532Vdc	448~560Vdc
重量	290Kg	430Kg	790Kg	810Kg



深圳昆宇电源科技有限公司

网址:WWW.COSPOWERS.COM

地址:深圳市宝安区燕罗街道罗田社区第三工业区广田路2号

电话:0755-33185898

版权及最终解释权归深圳昆宇电源科技有限公司所有

# DATA CENTER ENERGY STORAGE SERIES

COSPOWERS

5-15mins



- 1 Good high-temperature performance, no need for air conditioning cooling below 40°C, saves energy.
- 2 The PACK module is designed with a modular standard, allowing for flexible combinations and easy maintenance.
- 3 It has a long cycle life, with 3000 cycles at 0.5C/0.5C, 80% DOD, at 25°C.
- 4 The touch LCD provides an intuitive display of various parameters, records, status, and alarms.
- 5 It supports parallel operation of multiple units and cabinet-level fire protection.
- 6 It supports two-line design to meet the requirements of UPS models.
- 7 It features a three-level BMS management system, ensuring the safe and reliable operation of the system from the cell level to the system level.
- 8 It has a high energy density, saving 70% of the floor space compared to lead-acid batteries.

## Product parameters

Product model	CF24050U	CF48050U	CF486100U	CF512100U
Cell material			LFP	
Nominal voltage	240Vdc	480Vdc	486.4Vdc	512Vdc
Rated charging voltage	262.5Vdc	525Vdc	532Vdc	560Vdc
Nominal capacity	50Ah/12kWh	50Ah/24kWh	100Ah/48.64kWh	100Ah/51.2kWh
Self-discharge rate		≤3% (0~30°C/3 months)		≤3% (0~30°C/3 months)
Standard discharge current	50A Continuous discharge(1C)	50A Continuous discharge(1C)	100A Continuous discharge(1C)	100A Continuous discharge(1C)
Maximum discharge current	300A Continuous discharge(6C)	300A Continuous discharge(6C)	600A Continuous discharge(6C)	600A Continuous discharge(6C)
Standard charging current	25A(0.5C)	25A(0.5C)	50A(0.5C)	50A(0.5C)
Maximum charging current	50A(1C)	50A(1C)	100A(1C)	100A(1C)
Cycle life		3000 times @80%DOD, 0.5C/0.5C		
Communication interface		CAN; RS485; Dry contact		
Protection functions		Over-temperature, over-current, short circuit, over-charging, over-discharging, etc.		
Dimensions (W*D*H)	600*800*1400mm	600*800*2000mm	600*800*2200mm	600*800*2200mm
Certifications			UN	
Environment				
Storage temperature	0~40°C			
Operating temperature	15~45°C (Recommended operating temperature: 20~25°C)			
Relative humidity	5~95%			
Altitude	≤2000m			
Cell Specifications				
Nominal capacity	50Ah	50Ah	50Ah	50Ah
Nominal voltage	3.2Vdc	3.2Vdc	3.2Vdc	3.2Vdc
Working voltage range	2.5~3.6Vdc	2.5~3.6Vdc	2.5~3.6Vdc	2.5~3.6Vdc
Battery Module Specifications				
Configuration	1P15S	1P15S	2P20S/2P18S	2P20S
Nominal voltage	48Vdc	48Vdc	64/57.6Vdc	64Vdc
Working voltage range	42~52.5Vdc	42~52.5Vdc	56~70Vdc/50.4~63Vdc	56~70Vdc
Battery Pack Specifications				
Configuration	1P75S	1P150S	2P152S	2P160S
Nominal capacity	50Ah	50Ah	100Ah	100Ah
Nominal voltage	240Vdc	480Vdc	486.4Vdc	512Vdc
Working voltage range	210~262.5Vdc	420~525Vdc	425.6~532Vdc	448~560Vdc
Weight	290Kg	430Kg	790Kg	810Kg



Shenzhen Coslight Power Technology Co., Ltd.

W:WWW.COSPOWERS.COM

A:No.2,Guangtian Road, No.3 Industrial Zone, Luotian Community, Yanluo Street, Baoan District, Shenzhen, Guangdong Province, P.R.C

T:+86-755-33185898

Copyright and final interpretation rights belong to Shenzhen Coslight Power Technology Co., Ltd.