

# PowerTile-CS5000H-X-P 堆栈式储能电源

昆宇电源  
COSPOWERS



1 家居化风格，优雅美观

2 多种工作模式（光伏优先、市电优先、逆变优先）

3 简易安装和维护，即插即用

4 自带ISO/Android.App监控

5 单个电池5.12kWh，可扩展至20.48kWh

6 多重保护及告警系统，安全可靠

	参数/型号	CS5000H-5-P	CS5000H-10-P	CS5000H-15-P	CS5000H-20-P
逆变输出	额定输出功率		5500W		
	最大峰值功率		11000VA		
	额定输出电压		230Vac 单相		
	频率		50/60±0.3Hz		
	切换时间		10ms		
PV输入参数	MPPT数量		2		
	PV开路电压		500/500V		
	最大输入功率		4000+4000W		
	MPPT电压范围		120~450Vdc		
	最大PV输入电流		16/16A		
	最大短路电流		27/27A		
市电/发电机输入	输入电压范围		90~280Vac		
	输入频率范围		50/60Hz		
	最大旁路电流		40A		
电池参数	电池类型		LFP		
	电池额定电压		51.2		
	电压范围		46.4~58.4V		
	电池电量	5.12kWh	10.24kWh	15.36kWh	20.48kWh
	最大充/放电倍率		0.5/1C		
工作条件	充电温度范围		5~55°C		
	放电温度范围		-15~60°C		
	湿度		5~95%		
	散热方式		智能风冷		
	重量	107Kg	157Kg	207Kg	257Kg
	尺寸 (W*D*H)	725*515*445mm	725*515*585mm	725*515*725mm	725*515*865mm
	通讯方式		WIFI/RS485		
其它参数	认证		IEC62619、IEC62109、CE-EMC		



深圳昆宇电源科技有限公司

网址:WWW.COSPOWERS.COM

地址:深圳市宝安区燕罗街道罗田社区第三工业区广田路2号

电话:0755-33185898

版权及最终解释权归深圳昆宇电源科技有限公司所有

# PowerTile-CS5000H-X-P

COSPOWERS

## LOW VOLTAGE STACK-BASED ENERGY STORAGE POWER SUPPLY



- ① Homestyle design, elegant and beautiful
- ② Multiple working modes (solar priority, utility priority, inverter priority)
- ③ Easy installation and maintenance, plug and play
- ④ Possess ISO/Android. App to monitor
- ⑤ Single battery 5.12kWh, expandable up to 20.48KWh
- ⑥ Multiple protection and alarm system, safe and reliable

	Parameters/ Model	CS5000H-5-P	CS5000H-10-P	CS5000H-15-P	CS5000H-20-P
Inverter output	Rated output power		5500W		
	Peak power		11000VA		
	Rated output voltage		230Vac Single-phase		
	Frequency		50/60±0.3Hz		
	Switching time		10ms		
PV input parameters	Number of MPPTs		2		
	PV open-circuit voltage		500/500V		
	Maximum input power		4000+4000V		
	MPPT voltage range		120~450Vdc		
	Maximum PV input current		16/16A		
	Maximum short-circuit current		27/27A		
Mains/generator input	Input voltage range		90~280Vac		
	Input frequency range		50/60Hz		
	Maximum bypass current		40A		
Battery Parameters	Battery type		LFP		
	Battery rated voltage		51.2		
	Voltage range		46.4~58.4V		
	Battery capacity	5.12kWh	10.24kWh	15.36kWh	20.48kWh
	Maximum charge/discharge rate		0.5/1C		
Operating conditions	Charging temperature range		5~55°C		
	Discharging temperature range		-15~60°C		
	Humidity		5~95%		
	Cooling method		Air cooling		
	Weight	107Kg	157Kg	207Kg	257Kg
	Size (W*D*H)	725*515*445mm	725*515*585mm	725*515*725mm	725*515*865mm
	Communication method		WIFI/RS485		
Others	Certification		IEC62619, IEC62109, CE-EMC		



Shenzhen Coslight Power Technology Co., Ltd.

W:WWW.COSPOWERS.COM

A:No.2, Guangtian Road, No.3 Industrial Zone, Luotian Community, Yanluo Street, Baoan District, Shenzhen, Guangdong Province, P.R.C

T:+86-755-33185898

Copyright and final interpretation rights belong to Shenzhen Coslight Power Technology Co., Ltd.